


inserti Rivpren

NPTC - fam. 34800

inserto filettato in ottone
 corpo: neoprene
 testa: tonda



codice	d	ø foro	D	T	k	spessore serrabile	L			
		mm	mm	mm	mm	mm	mm	pz	kg	pz
23944	M3	8,0÷8,3	7,90	11,0	1,40	0,4÷4,0	12,60			24
23945	M4	8,0÷8,3	7,90	11,0	1,40	0,4÷4,0	12,60			0
23946	M5	9,7÷9,9	9,60	12,7	0,90	0,4÷4,9	14,40			12
23947	M5	9,7÷9,9	9,60	12,7	0,90	4,0÷11,6	21,50			0
23948	M5	9,7÷9,9	9,60	12,7	1,30	7,9÷16,0	26,10			12
23949	M5	9,7÷9,9	9,60	12,7	1,30	20,5÷30,0	39,80			8
23950	M6	12,8÷13,0	12,70	16,0	1,30	0,4÷2,8	16,00			8
23952	M6	12,8÷13,0	12,70	17,5	4,75	0,8÷4,7	21,10			8
23953	M6	12,8÷13,0	12,70	16,3	2,00	6,4÷11,5	26,70			0
23954	M6	13,1÷13,3	13,00	16,0	1,30	11,5÷23,0	35,00			8
23955	M8	16,0÷16,2	15,90	22,1	3,20	0,4÷4,0	18,30			12
23956	M8	16,0÷16,2	15,90	22,1	5,72	4,0÷9,5	27,90			8
23957	M8	18,1÷18,3	18,00	20,0	1,60	15,0÷39,0	50,00			0
23958	M10	20,1÷20,3	24,00	27,0	1,30	19,0÷40,0	55,00			6
23959	M12	24,1÷24,3	24,00	27,0	1,30	38,0÷64,0	80,00			6



Rivit s.r.l.
 via Marconi 20, loc. Ponte Rizzoli 40064 Ozzano dell'Emilia Bologna,
 tel. 051 4171129 fax 051 4171111 rivit@rivit.it www.rivit.it

